



- 01. POSTS ARE TO BE INSTALLED AT ALL INTERSECTING TITLE BOUNDARIES AND
- A COMPLETE WING OF STANDARD PALING FENCE @ 1.800MM HEIGHT.

 02. WHERE FENCE ABUTTS EASEMENTS, OR IN HIGH WIND AREAS (AS DETERMINED BY A COUNCIL OFFICER) POST DEPTH TO BE INCREASED TO 1200MM.
- 03. MINIMUM CONCRETE STRENGTH OF 25MPA AT 28 DAYS.

Α	2/11/15	ORIGINAL ISSUE	S.W.	S.P.	
REV.	DATE	REVISION DESCRIPTION	DRN.	APPD.	

WENTWORTH SHIRE COUNCIL

WORTH 亚 DRIVE

STANDARD DRAWINGS

NOISE-ABSORBING HIGH WIND TREATED PINE FENCE

GENERAL NOTES:

Drawing name: DRAWING NOT TO BE SCALED.
 ALL MEASUREMENTS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.
 FOR UP-TO-DATE DRAWINGS PLEASE CONTACT WENTWORTH SHIRE COUNCIL (WSC) OR CHECK THE WSC WEBSITE. 4. ALL STANDARD DRAWINGS ARE TO BE USED IN CONJUNCTION WITH SD1-1 (STANDARD DRAWINGS CONDITIONS OF USE).

DATE CREATED

2/11/15

DRG. NO: SD11-5A

Α