

NOTES:

- INVERT LEVEL OF PIPE/CULVERT TO MATCH EXISTING INVERT LEVEL OF OPEN DRAIN UNLESS OTHERWISE SPECIFIED BY WENTWORTH SHIRE COUNCIL OFFICER.
- 300mm MINIMUM COVER TO TOP OF PIPE.
- 3. 100mm MINIMUM BEDDING DEPTH.
- CONCRETE STRENGTH OF 25MPa AT 28 DAYS.

္ဗြ											
uments					WENTWORTH	STANDARD DRAWINGS					
ny doc					SHIRE COUNCIL	DUDAL VEHICLE					
٤	A 20/10/1	5 ORIGINAL ISSUE	S.W.	S.P.	WORTH 亚 DRIVE	RURAL VEHICLE					
ا	REV. DATE	REVISION DESCRIPTION	DRN.	APPD			LRU	SSING			
Jame	GENERAL N 1. DRAWING	<u>IOTES:</u> i NOT TO BE SCALED. SUIDEMENTS ADE IN MILLIMETRES	IINII E	ссст	ATED OTHERWISE. "WORTH SHIRE COUNCIL (WSC) OR CHECK THE WSC WEBSITE.						
<u>n</u>	3. FOR UP-	TO-DATE DRAWINGS PLEASE CO	NTACT	WEN.	WORTH SHIRE COUNCIL (WSC) OR CHECK THE WSC WEBSITE.	DATE CREATED:	DRG. NO:	<u> </u>	REV:	_	
raw	4. ALL STA USE).	NDARD DRAWINGS ARE TO BE US	SED IN	CONJU	INCTION WITH SD1-1 (STANDARD DRAWINGS CONDITIONS OF	20/10/15		SD4-6		Α	