



- THICKNESS OF PERMEABLE SUB-BASE AND SHOULDER AS PER DRAWINGS.
- MINIMUM GRADE OF SUBSURFACE DRAINS TO BE 1 5.
- WHERE AGRICULTURAL DRAINS TO BE PROVIDED 6. UNDER KERB, NO FINES CONCRETE TO BE USED AS
- TEMPORARY SUBSURFACE DRAIN & KERB TO BE REMOVED WHEN FUTURE PAVEMENT IS BEING CONTRUCTED.

## documents\0work\0jobs\3WC\standards development\standard drawings\SD7-2 REV A.dwg WENTWORTH SHIRE COUNCIL WORTH Ⅲ DRIVE REV. DATE REVISION DESCRIPTION GENERAL NOTES: DRN. APPE name:

TEMPORARY EDGE STRIP

## STANDARD DRAWINGS

SUBSURFACE DRAINAGE AT PAVED & ABUTTING PAVEMENTS, TEMP ROAD ENDS & ROAD CROSSINGS

DATE CREATED SD7-2 30/10/15

201

(06 Nov,

 DRAWING NOT TO BE SCALED.
ALL MEASUREMENTS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.
FOR UP-TO-DATE DRAWINGS PLEASE CONTACT WENTWORTH SHIRE COUNCIL (WSC) OR CHECK THE WSC WEBSITE. . ALL STANDARD DRAWINGS ARE TO BE USED IN CONJUNCTION WITH SD1-1 (STANDARD DRAWINGS CONDITIONS OF USE).